



# BSPET PET expandable braided sleeving

## Applications

Designed from PET monofilament yarns, high ratio expansion enables quick and easy installation over wires. It's mainly used in industrial wire bundle, and cable protection.

## Operating temperature range

Operating temperature :

BSPET: -50°C ~ 125°C

BSPETFR: -50°C ~ 150°C

UL file no. E304566

## Product Dimensions

Flame retardant material

Part No.	Nominal Size	Expansion Range DIA		Ends	Packing Feet(M)/R
	mm	Min(mm)	max(mm)		
BSPETFR0032-1	3.2±1	2.37	6.35	1	1000ft(305 M )/R
BSPETFR0064-3	6.4±2	3.17	9.53	3	1000ft(305 M )/R
BSPETFR0095-3	9.5±2	4.76	15.88	3	500ft(153 M)/R
BSPETFR0127-3	12.7±2	6.35	19.05	3	500ft(153 M)/R
BSPETFR0191-3	19.1±3	12.70	31.75	3	250ft(77 M)/R
BSPETFR0320-3	32.0±3	19.05	38.1	3	250ft(77 M)/R
BSPETFR0381-4	38.1±3	25.4	57.15	4	200ft(61 M)/R
BSPETFR0445-4	44.5±3	31.75	69.85	4	200ft(61 M)/R
BSPETFR0500-5	50.0±3	44.5	75	5	200ft(61 M)/R